


PRODUCT: AQUATIC CLEAR DROP

TARGET: MURKY WATER





Clears murky dam water

Clears microscopic organisms

Leaves your water crystal clear



Aquatic Clear Drop is a budget granular flocculant, best suited to working water bodies free of fish and wildlife, such as Ornamental Ponds.

WHY CHOOSE CLEAR DROP?

- Fast-acting (results in just 36 hours)
- Perfect for fast-flowing water
- Cost-effective
- Suitable for both domestic and commercial use

Aquatic Clear Drop is a granular flocculant designed to remove suspended clay, silt, fine organic matter, microscopic organisms & algae from the water column, improving clarity and the overall health of your water.

WHY SHOULD I USE AQUATIC CLEAR DROP?

Highly turbid water is unsafe to swim in as it greatly reduces water clarity and visibility, it is unpleasant for livestock to drink from water that contains a lot of sediment, turbid water can cause blockages in your pipes and not to mention makes the water unsightly. By using Aquatic Clear Drop, it improves the clarity and quality of your water!



Swimming, Irrigation & Stock.

BUY ONLINE





For more information visit

WWW.AQUATICTECHNOLOGIES.COM.AU

This easy-to-apply product is made for clearing up murky water in dams, ponds, lakes and more.

Organic matter, microscopic organisms & some forms of algae harbour waterborne diseases & pathogens. Aquatic Clear Drop can assist in removing these particles from suspension & improving water health.

1kg of Aquatic Clear Drop treats 25,000L of water.

To calculate rectangular volume: LxWxH = volume (m3)

To get volume in L: m3 x 1000



SUITABLE FOR









APPLICATION RATES

AQUATIC TECHNOLOGIES		The Water Treatment Experts	
Aquatic Clear Drop Application Rates			
Where to use	How Much To Use	Application Methods (#1 is Optimal)	When To Use
Dams and Ponds	Dissolve product 10:1 20kg will treat 500,000L/ Half ML.	1. Dissolve the recommended amount of product with 1kg product into 10L of water into a sprayer & spray over the dam's surface as evenly as possible. 2. Sprinkle the recommended amount of product over dam's surface as evenly as possible. 3. Dissolve the recommended amount of product with water into a container or bucket & tip over the dam's surface as evenly as possible. Allow 24-36 hours to settle to the bottom.	Once. If water remains murky, apply a second treatment after 72 hours.

*Always read the product label for directions.

FOR BEST RESULTS Dissolve product 10:1 and spray over water's surface (application method 1). pH range should sit between 7-8.5.

